

SI		IP		Friction Loss (FT/100FT)
Dim in Flow rate mm^3/min	L/S	Dim (in)	Flow rate GPM	
20	0-0.25	3/4"	0-4	0.5-4
25	0.25-0.47	1"	4.5-7.5	1.25-3.4
32	0.5-1	1 1/4"	8-16	1.25-4
40	1.04-1.5	1 1/2"	16.5-24	1.75-4
50	1.55-3	2"	24.5-48	1.25-4.4
65	3.13-4.86	2 1/2"	48.5-77	1.75-4
80	4.89-8.8	3"	77.5-140	1.4-4.4
100	8.9-17.7	4"	141-280	1.2-4.6
125	17.73-31.55	5"	281-500	1.5-4
152	31.6-50.47	6"	501-800	1.65-4
200	50.5-107.25	8"	801-1700	1-4
250	107.3-157.7	10"	1701-2800	1.4-2.5
300	157.8-227	12"	2501-3600	1.2-2.2
350	227.2-265	14"	3601-4200	1.4-1.8
400	265.1-347	16"	4201-5500	0.95-1.7
450	347.1-441.6	18"	5501-700	0.95-1.4
500	441.7-567.8	20"	7001-9000	0.8-1.25
600	567.9-820.2	24"	9001-1300	0.55-1.2